

## How to Template for Radius Casing

### Ensure Job Site is Ready:

- ❖ Confirm address and access to building
  - Meeting someone
  - Access code
  - Door open
- ❖ Confirm need for:
  - Scaffolding
  - Ladder
  - Additional person
- ❖ Openings have jambs applied  
(Unless we are providing jamb & casing)



### Supplies Needed:

- ❖ Rosin paper
- ❖ Tape measure
- ❖ Utility knife/scissors
- ❖ Push pins
- ❖ Writing tool (fine point, i.e. pen)
- ❖ Labels
- ❖ Ladder (if not available on site)



### Templating Process:

- Measure opening width to determine length of rosin paper needed
- Measure and cut rosin paper approximately 6"-8" wider than opening dimension
- Set up/secure ladder or scaffolding in front of opening
- Gather enough push pins to place every 6"-8", close to jamb for stability as well as for casing to cover holes
- On *smaller* units, start in center and secure a midpoint push pin. Proceed to secure each direction of the paper to unit every 6"-8"
- On *larger* units where you will need to move the ladder, start securing the paper with push pins at one end of the unit and work your way to the other end
- Once the rosin paper is secured, run your thumb across the entire edge/inside of jamb continuing down the leg approximately 2", leaving a crease of the radius of the unit.



- After ensuring that you have a distinct crease mark, remove the push pins and remove paper
- With the rosin paper laid out on the floor, with a pen (avoid wide-tip markers) mark where the radius and straight edge/leg meet at each end. At that point, write on the rosin paper how many inches you'd like the jamb/casing to extend, which will help with mitering.



- Write the necessary information on the rosin paper:
  - o Company name
  - o Your name
  - o Job name
  - o Wood species
  - o Room location
  - o Quantity
  - o Profile (if known)
  - o PO (if known)

*And that's it!*

*Any Questions? Call (920)788-9322*